

# Wohler VIS 350 Service Camera

## TECHNICAL DATA

### Monitor

Dimensions housing.....7" x 4.5" x 1.3"  
 TFT-Display.....7" / 16:9 format  
 Video-Out.....FBAS signal  
 Weight.....1 lbs

### Power Supply

Power supply.....Space for 2 rechargeable batteries, each 12 V or  
 via power pack  
 Battery operating time.....Max. 2 rechargeable batteries, each 120 mins. = 4 h  
 (battery status in display)

### Pan & tilt 1.5" dia color camera head

Type.....1/3" COLOR CMOS  
 Pixels.....656 x 492 (NTSC)  
 Light sensitivity.....0.5 Lux  
 Lens.....f = 0.09", F = 2.5  
 Viewing angle.....115°  
 Light source.....12 white LEDs  
 Degree of protection.....Waterproof to IP 67  
 Dimensions.....1 1/2" dia x 2"  
 Operating temperature.....32...104 °F, RH 95 % MAX  
 Storage temperature.....-4...122 °F, RH 95 % MAX

### Locator transmitter

Transmission frequency.....8.9 kHz

### Push rod

Length.....100 ft.  
 Diameter.....0.33"

### Plastic case

Dimensions.....20" x 17" x 7" (l x w x h)  
 Weight.....18 lbs

### Distance measurement

Wohler VIS 350 / VIS 300.....Electronic meter counter

### Locator receiver

Display.....Graphic visualization of transmitted position

### Output impedance

Headphones.....32 Ohm  
 Power supply.....12 V MIMH battery (rechargeable)  
 Operating temperature.....32...104 °F  
 Storage temperature.....14 °F...104 °F  
 Weight.....1.3 lbs  
 Dimensions.....13" x 6" x 3" cm (l x w x h)

### Memory (Wohler VIS 350)

Recording.....4 GB SD card (2.5 h recording capacity)  
 Interface.....Mini USB port